



SHENZHEN GREPOW BATTERY CO.,LTD.

TEL: +86 755 29045795

[HTTP://www.grepow.cn](http://www.grepow.cn)

Date: Jan 04,2017

FAX: +86 755 61558171

E-MAIL:fangchaojun@china.com

Report No:GRP-MSDS-20170104003

MATERIAL SAFETY DATA SHEET REPORT

Model No.8334096 3200mAh 3.7V 11.84Wh

ADD: WUSHIGANG, CHUANGYIROAD, TONGFUYUINDUSTRIALPARK, LONGHUA VILLAGE,
BAOANDISTRICT, SHENZHEN, CHINA



SHENZHEN GREPOW BATTERY CO.,LTD.

TEL: +86 755 29045795

FAX: +86 755 61558171

[HTTP://www.grepow.cn](http://www.grepow.cn)

E-MAIL:fangchaojun@china.com

Date: Jan 04 2017

Report No:GRP-MSDS-20170104003

Section 1. Product Identification

Product Name:	Rechargeable lithium polymer battery
Company of Producing:	ShenZhen Grepow Battery Co.,Ltd
Models:	8334096 3200mAh 3.7V 11.84Wh
Address:	1ST to 3rd floor of complex building,1st to 4th floor of 2nd building,1st to 4th floor of 1st building, Gaofeng community,Dalang Street,Baoan District,Shenzhen City,Guangdong Province,P.R.China
Tel:	0755-29045795
Fax:	0755-61558171
Post code:	518100

Section 2. Hazards Identification

No harm at the normal use. If contact the electrolyte in the battery, reference as follows:

Classification of the substance or mixture

Classification according to GHS

Acute toxicity, Oral (Category 4)

Acute toxicity, Dermal (Category 3)

Skin, irritate (Category 1B)

Eyes, irritate (Category 1)

Label elements

Labelling according to Regulation (EC) No 1272/2008[CLP]

Signal word: Danger

Hazard statement(s): H311: Toxic in contact with skin.
H314: Causes severe skin burns and eye damage
H302: Harmful if swallowed.

Precautionary statement(s):

Prevention: P280: Wear protective gloves/protective clothing/eye protection / face protection.

Response: P312: Call a POISON CENTER or doctor/ physician if you feel unwell. P302 + P350 - IF ON SKIN: Gently wash with plenty of soap and water P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Disposal: P501: Dispose of contents/container in accordance with local/national regulations

Other hazards No information available.

Section 3. Composition,Information on Ingredients

Composition	CAS NO	EC#	Weight (%)
Lithium Cobalt Oxide	12190-79-3	235-362-0	32.6%
PVDF	24937-79-9	200-867-7	0.7%
Graphite	7782-42-5	231-955-3	16.5%
Electrolyte	---	---	16.5%
CMC	9004-32-4	900-432-4	0.3%

ADD: WUSHIGANG, CHUANGYIROAD, TONGFUYUINDUSTRIALPARK, LONGHUA VILLAGE,
BAOANDISTRICT, SHENZHEN, CHINA



SHENZHEN GREPOW BATTERY CO.,LTD.

TEL: +86 755 29045795

FAX: +86 755 61558171

[HTTP://www.grepow.cn](http://www.grepow.cn)

E-MAIL:fangchaojun@china.com

Date: Jan 04,2017

Report No:GRP-MSDS-20170104003

PP+PE	9003-07-0	---	3.6%
Copper Foil	7440-50-8	231-159-6	17.6%
Aluminum Foil	7429-90-5	231-072-3	8.7%
Aluminum	7429-90-5	231-072-3	0.25%
Nickel	7440-02-0	231-853-9	0.85%
SBR	9003-55-8	---	0.8%
Carbon	1333-86-4	231-153-3	1.6%

Weight of metallic lithium per cell: 58.0 ± 2.0 g . There is no metallic lithium in the lithium polymer battery.
The lithium polymer battery is with a watt-hour rating: ≤ 20 Wh/Cell(cell), ≤ 100 Wh(battery pack)

Section 4. First Aid Measures

Description of first aid measures

General information No special measures required.

After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

After inhalation

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

After swallowing

Do not induce vomiting. Get medical attention.

Information for doctor:

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Section 5. Fire Fighting Measure

Flammability: Not available.

Extinguishing media

Suitable extinguishing agents

Use extinguishing agent suitable for local conditions and the surrounding environment Such as dry powder , CO₂.

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150°C(302°F)), when damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

ADD: WUSHIGANG, CHUANGYIROAD, TONGFUYUINDUSTRIALPARK, LONGHUA VILLAGE,
BAOANDISTRICT, SHENZHEN, CHINA



SHENZHEN GREPOW BATTERY CO.,LTD.

TEL: +86 755 29045795

FAX: +86 755 61558171

[HTTP://www.grepow.cn](http://www.grepow.cn)

E-MAIL:fangchaojun@china.com

Date: Jan 04,2017

Report No:GRP-MSDS-20170104003

Advice for firefighters

Protective equipment: Wear self-contained respirator. Wear fully protective impervious suit.

Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

Environmental precautions

Do not allow material to be released to the environment without proper governmental permits.

Steps to be taken in case material is spilled or released

Remove ignition sources, evacuate area. Sweep up using a method that does not generate dust. Collect as much of the spilled material as possible, placed the spilled material into a suitable disposal container. Keep spilled material out of sewers, ditches and bodies of water.

Waste disposal method

All waste must refer to the United Nations, the national and local regulations for disposal.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7. Handling and storage

Handling

Precautions for safe handling

Consumption of food and beverage should be avoided in work areas.

Wash hands with soap and water before eating, drinking.

Ground containers when transferring liquid to prevent static accumulation and discharge.

Information about fire and explosion protection

Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles

Store in a cool, dry, well-ventilated place.

Information about storage in one common storage facility

ADD: WUSHIGANG, CHUANGYIROAD, TONGFUYUINDUSTRIALPARK, LONGHUA VILLAGE,
BAOANDISTRICT, SHENZHEN, CHINA



SHENZHEN GREPOW BATTERY CO.,LTD.

TEL: +86 755 29045795

[HTTP://www.grepow.cn](http://www.grepow.cn)

Date: Jan 04,2017

FAX: +86 755 61558171

E-MAIL:fangchaojun@china.com

Report No:GRP-MSDS-20170104003

Keep away from heat, avoiding the long time of sunlight.

Further information about storage conditions

Keep container tightly sealed.

Specific and use

No further relevant information available.

Section 8. Exposure Controls, Person Protection

Control parameters

Ingredients with limit values that require monitoring at the workplace:

12190-79-3 Lithium Cobalt Oxide

TLV (USA)	0.02mg/m ³
-----------	-----------------------

MAK(Germany)	0.1mg/m ³
--------------	----------------------

Exposure controls

Personal protective equipment

General protective and hygienic measures

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Respiratory Protection

Use suitable respirator when high concentrations are present.

Section 9. Physical and Chemical Properties

Information on basic physical and chemical properties

General information

Appearance	Silver
------------	--------

Form:	quadrate
-------	----------

Odour:	Odorless
--------	----------

PH:	Not available
-----	---------------

Change in condition:	Not available
----------------------	---------------

Melting point:	Not available
----------------	---------------

Boiling point:	Not available
----------------	---------------

Freezing point:	Not available
-----------------	---------------

Flash point:	Not available
--------------	---------------

Flammability:	Not available
---------------	---------------

Ignition temperature:	Not available
-----------------------	---------------

Decomposition temperature:	Not available
----------------------------	---------------

Self-igniting	Not available
---------------	---------------

Danger of explosion:	Not available
----------------------	---------------

ADD: WUSHIGANG, CHUANGYIROAD, TONGFUYUINDUSTRIALPARK, LONGHUA VILLAGE,
BAOANDISTRICT, SHENZHEN, CHINA



SHENZHEN GREPOW BATTERY CO.,LTD.

TEL: +86 755 29045795

FAX: +86 755 61558171

[HTTP://www.grepow.cn](http://www.grepow.cn)

E-MAIL:fangchaojun@china.com

Date: Jan 04,2017

Report No:GRP-MSDS-20170104003

Explosion limits:	
Lower:	Not available
Upper:	Not available
Oxplosion limits:	Not available
Vapour pressure:	Not available
Density:	Not available
Relative density:	Not available
Vapour density:	Not available
Evaporation rate:	Not available
Solubility in/Mis cibility with water	Not available
n-octanol/water partition coefficient:	Not available
Viscosity:	Not available
Dynamic:	Not available
Kinematic:	Not available
Other information:	
Voltage:	3.7V
Electric capacity:	3200mAh

Section 10. Stability and Reactivity

Reactivity: Data not available.

Chemical stability: Stable.

Possibility of hazardous reactions: Data not available.

Conditions to Avoid

Flames, sparks, and other sources of ignition, incompatible materials.

Incompatibilities

Oxidizing agents, acid, base.

Hazardous Combustible Products

Carbon monoxide, carbon dioxide, lithium oxide fumes.

Hazardous Polymerization

N/A.

Section 11. Toxicological Information

Information on toxicological effects

Acute toxicity

LD/LC50 Values relevant for classification:

Not available.

Primary irritant effect

No further relevant information available.

ADD: WUSHIGANG, CHUANGYIROAD, TONGFUYUINDUSTRIALPARK, LONGHUA VILLAGE,
BAOANDISTRICT, SHENZHEN, CHINA



SHENZHEN GREPOW BATTERY CO.,LTD.

TEL: +86 755 29045795

FAX: +86 755 61558171

[HTTP://www.grepow.cn](http://www.grepow.cn)

E-MAIL:fangchaojun@china.com

Date: Jan 04,2017

Report No:GRP-MSDS-20170104003

Sensitization:

No further relevant information available.

Additional toxicological information:

Toxicological, metabolism and distribution:

No further relevant information available.

Acute effects (acute toxicity, irritation and corrosivity):

No further relevant information available.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

No further relevant information available.

Section 12. Ecological Information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability: No further relevant information available.

Behaviour in environmental systems

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Ecological effects

Additional ecological information

General notes:

Do not allow material to be released to the environment without proper governmental permits.

Other adverse effects: No further relevant information available.

Section 13. Disposal Considerations

Waste treatment methods

Recommendation:

Consult state, local or national regulations to ensure proper disposal.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

Section 14. Transport Information

According to the Packing Instruction 965 IATA DGR 58 Edition for transportation, or the special

ADD: WUSHIGANG, CHUANGYIROAD, TONGFUYUINDUSTRIALPARK, LONGHUA VILLAGE,
BAOANDISTRICT, SHENZHEN, CHINA



SHENZHEN GREPOW BATTERY CO.,LTD.

TEL: +86 755 29045795

FAX: +86 755 61558171

[HTTP://www.grepow.cn](http://www.grepow.cn)

E-MAIL:fangchaojun@china.com

Date: Jan 04,2017

Report No:GRP-MSDS-20170104003

provision 188 of IMDG, or the <<Recommendations On The Transport Of

Dangerous Goods-Model Regulations>> (18).

More information concerning shipping, testing, marking and packaging can be obtained from Label master at <http://www.labelmaster.com>.

Separate Lithium-ion batteries when shipping to prevent short-circuiting. They should be packed in strong packaging for support during transport. Take in a cargo of them without falling, dropping, and breakage. Prevent collapse of cargo piles and wet by rain.

Transport Fashion: By air, by sea, by railway, by road.

Section 15. Disposal Considerations

This Material Safety Data Sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Safety, health and environmental regulations/legislation specific for the substance or mixture

Composition	CAS#	TSCA	EC#	EINECS
Lithium Cobalt Oxide	12190-79-3	Listed	235-362-0	Listed
PVDF	24937-79-9	Listed	200-867-7	Listed
Graphite	7782-42-5	Listed	231-955-3	Listed
PP-PE	9003-07-0	Listed	---	Not Listed
Copper	7440-50-8	Listed	231-159-6	Listed
Aluminum	7429-90-5	Listed	231-072-3	Listed
Nickel	7440-02-0	Listed	231-853-9	Listed
SBR	9003-55-8	Listed	---	Not Listed
Carbon	1333-86-4	Listed	231-153-3	Listed

Section 16. Additional Information

Abbreviations and acronyms

CLP: EU regulation (EC) No 1272/2008 on classification, labelling and packaging of chemical substances and mixtures.

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

ACGIH: American Conference of Governmental Industrial Hygienists

TLV: Threshold Limit Value

IATA: International Air Transport Association

IMDG: International Maritime Dangerous Goods

LC50: lethal concentration, 50 percent kill

LD50: lethal dose, 50 percent kill

TWA: Time Weighted Average

TSCA: United States Toxic Substances Control Act Section 8(b) Inventory

ADD: WUSHIGANG, CHUANGYIROAD, TONGFUYUINDUSTRIALPARK, LONGHUA VILLAGE, BAOANDISTRICT, SHENZHEN, CHINA



SHENZHEN GREPOW BATTERY CO.,LTD.

TEL: +86 755 29045795

FAX: +86 755 61558171

[HTTP://www.grepow.cn](http://www.grepow.cn)

E-MAIL:fangchaojun@china.com

Date: Jan 04,2017

Report No:GRP-MSDS-20170104003

EINECS: European Inventory of Existing Commercial Chemical Substances
Model: Recommendations on the Transport of Dangerous Goods Model
Regulations: Regulations

Declare to reader

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

MSDS Creation Date: Jan 04, 2017

End of report

ADD: WUSHIGANG, CHUANGYIROAD, TONGFUYUINDUSTRIALPARK, LONGHUA VILLAGE,
BAOANDISTRICT, SHENZHEN, CHINA